## **Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of the claims in the application:

## **Listing of Claims:**

1. (Cancelled) A method, comprising:

determining information to be displayed on a display of a computer system by sensing movement of the computer system;

tracking the movement of the computer system via physical contact with a surface; and

correlating the tracked movement of the computer system to an indicator on the display of the computer system.

- 2. (Cancelled) The method of claim 1, wherein said sensing the movement of the computer system is performed using a movement sensor.
- 3. (Cancelled) The method of claim 2, wherein the movement sensor is an optical sensor.
- 4. (Cancelled) The method of claim 3, wherein said sensing the movement of the computer system is performed when the computer system is placed on the surface.
- 5. (Cancelled) The method of claim 2, wherein the movement sensor is a mechanical sensor.
- 6. (Cancelled) The method of claim 5, wherein said sensing the movement of the computer system is performed when the computer system is on the surface or handheld.
- 7. (Cancelled) The method of claim 1, wherein said sensing the movement of the computer system comprises sensing direction of the movement of the computer system.

- 8. (Cancelled) The method of claim 7, wherein said determining the information to be displayed on the display comprises determining the information consistent with said sensed direction of the movement of the computer system.
- 9. (Cancelled) The method of claim 1, further comprising:

determining an action to be performed by the computer system by sensing a clicking motion of the computer system.

- 10. (Cancelled) The method of claim 9, wherein the clicking motion of the computer system is initiated by applying pressure on an upper section of the computer system toward a lower section of the computer system.
- 11. (Cancelled) The method of claim 1, wherein said determining the information to be displayed on the display of the computer system comprises determining a location of a cursor.
- 12. (Cancelled) A computer readable medium having stored thereon sequences of instructions which are executable by a system, and which, when executed by the system, cause the system to perform a method, comprising:

determining information to be displayed on a display of a computer system by sensing direction of movement of the computer system;

tracking the movement of the computer system via physical contact with a surface; and

correlating the tracked movement of the computer system to an indicator on the display of the computer system.

13. (Cancelled) The computer readable medium of claim 12, wherein the direction of movement of the computer system is sensed using an optical sensor or a mechanical sensor.

- 14. (Cancelled) The computer readable medium of claim 12, wherein the information to be displayed on the display of the computer system includes a first section of a document, and wherein the sensed direction of movement of the computer system is used to display a second section of the document.
- 15. (Cancelled) The computer readable medium of claim 14, wherein a logical location of the second section relative to the first section is consistent with the sensed direction of the movement of the computer system.
- 16. (Cancelled) The computer readable medium of claim 12, wherein the action to be performed by the computer system corresponds to an action performed when a mouse click is initiated.
- 17. (Cancelled) A system, comprising:
  - a processor;
  - a display coupled to the processor;
- a first movement sensor coupled to the processor, the first movement sensor is to sense direction of movement of the system; and
- a translation logic to translate the direction of movement of the system into a first set of operations to be performed by the processor, wherein the first set of operations includes displaying information on the display consistent with the sensed direction of movement of the system, tracking the movement of the computer system via physical contact with a surface, and correlating the tracked movement of the computer system to an indicator on the display of the computer system.
- 18. (Cancelled) The system of claim 17, wherein the translation logic is further to translate clicking motion of the system into a second set of operations to be performed by the processor, wherein the second set of operations corresponds to an action performed when a mouse click is initiated.
- 19. (Cancelled) The system of claim 18, wherein said clicking motion is initiated by

applying pressure to an upper section of the system toward a lower section of the system, wherein said upper section includes the display, and wherein said lower section includes the movement sensor.

- 20. (Cancelled) The system of claim 17, wherein the movement sensor is an optical sensor or a mechanical sensor.
- 21. (Cancelled) The system of claim 17, further comprising a second movement sensor coupled to the first movement sensor.
- 22. (Cancelled) The system of claim 21, wherein angular rotation is determined by using directional information sensed by the first movement sensor and the second movement sensor.
- 23. (Cancelled) A method, comprising:

navigating information displayed on a display of a computer system by causing a first movement sensor to sense movement of the computer system; and

tracking the movement of the computer system via physical contact with a surface.

- 24. (Cancelled) The method of claim 23, further comprising:
- controlling position of a cursor displayed on the display of the computer system by causing the first movement sensor to sense movement of the computer system.
- 25. (Cancelled) The method of claim 23, further comprising:

determining angular rotation of the computer system by causing the first movement sensor and a second movement sensor to sense movement of the computer system.

26. (Cancelled) The method of claim 23, further comprising: recognizing a mouse click action when an upper section of the computer system is

displaced toward a lower section of the computer system.

27. (Cancelled) The method of claim 23, wherein the first movement sensor is an optical sensor or a mechanical sensor.

## 28. (Newly added) A method, comprising:

sensing a directional movement of a computer system on a surface via a first movement sensor; and

adjusting information displayed on a display of the computer system, wherein the information displayed is independent from the surface, and the adjusting is correlated to the directional movement of the computer system.

- 29. (Newly added) The method of claim 28, wherein the first movement sensor is an optical sensor or a mechanical sensor.
- 30. (Newly added) The method of claim 28, wherein the directional movement comprises angular rotation of the computer system sensed by the first movement sensor and a second movement sensor;
- 31. (Newly added) The method of claim 28, further comprising:

correlating the directional movement of the computer system to a cursor movement on the display of the computer system.

32. (Newly added) The method of claim 28, further comprising:

sensing external pressure on a first section of the computer system toward a second section of the computer system, wherein the first section of the computer system comprises the display, the second section of the computer system comprises the first movement sensor, and the first section of the computer system substantially overlaps the second section of the computer system; and

translating the external pressure to a mouse click action for the computer system.

33. (Newly added) A method, comprising:

sensing external pressure on a first section of a computer system toward a second section of the computer system, wherein the first section of the computer system comprises a display, and the first section of the computer system substantially overlaps the second section of the computer system; and

translating the external pressure to a mouse clicking action for the computer system.

- 34. (Newly added) The method of 33, wherein the second section of the computer system comprises a movement sensor.
- 35. (Newly added) The method of 33, wherein the external pressure may be applied toward perimeter of the first section of the computer system.
- 36. (Newly added) The method of 33, wherein the external pressure may be applied toward center of the first section of the computer system.
- 37. (Newly added) A computer-readable storage medium having stored thereon sequences of instructions which are executable by a computer system, and which, when executed by the computer system, cause the computer system to perform a method, comprising:

sensing a directional movement of the computer system on a surface via a movement sensor; and

adjusting information displayed on a display of the computer system, wherein the information displayed is independent from the surface, and the adjusting is correlated to the directional movement of the computer system.

38. (Newly added) A computer-readable storage medium having stored thereon sequences of instructions which are executable by a computer system, and which, when executed by the computer system, cause the computer system to perform a method, comprising:

sensing external pressure on a first section of the computer system toward a second section of the computer system, wherein the first section of the computer system comprises a display, and the first section of the computer system substantially overlaps the second section of the computer system; and

translating the external pressure to a mouse clicking action for the computer system.